



**STANDARDS: DRAFT EN ISO 10545 - 17, ANNEX B, ASTM, C-1028-07**

### SCIVOLOSIMETRO STATICO PULL-METER SS ISO-ASTM

Strumento per la determinazione del coefficiente statico sulle superfici asciutte o bagnate. Lo strumento è adatto per eseguire prove su superfici bagnate o asciutte.

Il display dello strumento visualizza la misura della forza max di ogni misura in Kg e inoltre esegue il calcolo della media delle misure eseguite e il coefficiente di attrito.

Possibilità di collegamento al Pc o stampante tramite porta seriale RS-232.

### SLIPPERINESS STATIC PULL-METER SS ISO-ASTM

Instrument for the measure the dry and wet static coefficient of friction. This instrument is suitable for measured the static coefficient up the dry and wet surface.

The electronic control display shown the force friction in kg and the calculation the mean values and the static coefficient of friction.

Possibility to connect the instrument to a PC or printer via RS-232 port.

#### Specifiche tecniche:

- ◆ n°1 base di legno con gomma 4S per prova ISO 10545-17 annex B
- ◆ Box elettrico da tavolo con display LCD
- ◆ Cella di carico a trazione da 25 kg.
- ◆ Alimentazione: 230 V – 50/60 hz monofase
- ◆ n°2 basi in alluminio e gomma Neolite per prova ASTM C - 1028 - 07

#### Dotazione:

Valigia alluminio con strumento per prova ISO 10545-17 annex B

#### Accessori:

- GT0824 Kit per trasformazione da ISO a ASTM
- GT1090 Kit per trasformazione da ASTM a ISO
- GT0825 Kit calibrazione per ISO 10545 – 17 Annex B
- GT0826 Kit calibrazione per ASTM C-1028-07
- GT0260 Stampante esterna RS-232C
- GT0827 Base di legno con gomma 4S per ISO 10545 – 17 Annex B
- GT0828 Base in alluminio anodizzato con Neolite per ASTM C-1028-07
- GT0829 Detergente Hillyard's Renovator (quantità 50 cc)

#### Technical specifications:

- ◆ n°1 wooden base with rubber 4S for ISO 10545 – 17 annex B
- ◆ Electronic box with LCD display
- ◆ Traction load cell 25 kg.
- ◆ Supply: 230 V – 50/60 Hz single phase
- ◆ n° 2 aluminium base with Neolite rubber for ASTM C - 1028 - 07

#### Equipment:

Aluminium case with instrument for ISO 10545 – 17 annex B test

#### Accessories:

- GT0824 Kit to transform from ISO to ASTM
- GT1090 Kit to transform from ASTM to ISO
- GT0825 Kit calibration ISO 10545 – 17 Annex B
- GT0826 Kit calibration ASTM C-1028-07
- GT0260 External printer RS-232C
- GT0827 Wooden base with rubber 4S for ISO 10545 – 17 Annex B
- GT0828 Anodized aluminium base with Neolite for ASTM C-1028-07
- GT0829 Detergent Hillyard's Renovator (quantity 50 cc)

Codice Code	Modello Model	Dimensioni esterne Overall dimensions	Potenza Power	Peso Weight
GT0810	PULL-METER SS ISO	450 x 370 x 150 mm	23 W	9,5 kg
GT0966	PULL-METER SS ASTM	450 x 400 x 290 mm	23 w	30 KG